



Good looks. Great performance.

WINDOW ACs



Star Rated Window ACs



5 Star 1 TR / 1.5 TR
3 Star 1 TR / 1.5 TR
2 Star 1 TR / 1.5 TR / 2 TR

*Auto Mode not available



2 Star 1 TR / 1.5 TR

*Filter check LED available in
2 Star 1 TR & 1.5 TR



3 Star 1.5 TR
2 Star 0.75 TR / 1 TR



5 Star 1 TR / 1.5 TR
3 Star 1 TR / 1.5 TR
2 Star 1 TR / 1.5 TR / 2 TR

Blue Star's star rated range of Window ACs bring together the benefits of superior cooling, energy-saving performance and aesthetic looks, all in one unit. Available in 5 star, 3 star and 2 star ratings, these ACs offer you nothing but the best. With multi fan speed operation, an auto-restart with memory function, and dust filter, these ACs are specially designed keeping all your needs in mind.

Features



Multi-Fan Speed



Hydrophilic Blue Fins Evaporator



Dry Mode



Auto Restart with Memory Backup



Anti-Corrosive Blue Fin Condenser



On/Off Timer



Sleep Mode



Auto Mode*



Anti-Freeze Thermostat



Elegant Remote Control



Dust Filter

TECHNICAL SPECIFICATIONS

WAC - 2 STAR

Model No.		2WAE081YC	2W12GA	2W12LA	2WAE121YC	2W18LB	2W18GA	2WAE181YC	2W24LA
Performance Parameters	Nominal Capacity (TR)	0.75	1	1	1	1.5	1.5	1.5	2
	Voltage / Frequency / Phase	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single
	Cooling Capacity (Watt)	2515	3200	3170	3335	4860	4860	5275	5850
	Power Input (Watt)	925	1160	1170	1230	1750	1750	1930	2080
	EER (W / W)	2.72	2.76	2.71	2.71	2.78	2.78	2.73	2.81
	Star Rating - BEE Table 2.4	2 STAR	2 STAR	2 STAR	2 STAR	2 STAR	2 STAR	2 STAR	2 STAR
	Running Current (Amps)	4.0	4.96	5.2	5.4	8	7.26	8.22	9.5
	Moisture Removal (Litres/hour)	1	1.6	1.3	1.6	2.2	1.83	2.3	2.7
	Airflow Volume (Wet CFM) (High / Medium/ Low)	264 / 240 / 194	236 / 227 / 218	290 / 274 / 258	282 / 253 / 224	460 / 420 / 380	430 / 418 / 398	441 / 412 / 383	460 / 420 / 380
	Noise Level Indoor (High / Med / Low) In dB(A)	53 / 50 / 48	51 / 49 / 47	53 / 53 / 52	50 / 48 / 46	55 / 53 / 52	52 / 50 / 48	52 / 50 / 48	57 / 55 / 53
Dimensions and Weight	Dimension (W X H X D) mm	450 x 346 x 535	600 X 385 X 525	560 X 377 X 615	560 x 375 x 668	660 x 430 x 760	660 x 430 x 770	660 x 428 x 700	660 x 430 x 760
	Net Weight	28 Kg	41 Kg	42 Kg	47 Kg	58 Kg	56 Kg	58 Kg	61 Kg
Compressor	Compressor Type	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
	Compressor Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years
Refrigerant and Ambient Operations	Refrigerant	R 22	R 22	R 22	R 22	R 22	R22	R 22	R 22
	Max. Ambient Temp (°C)	46°C	46°C	46°C	46°C	46°C	46°C	46°C	46°C
Remote	Remote	LCD With Back Lit	LCD Remote	Simple Remote	LCD Remote	Simple Remote	LCD Remote	LCD Remote	Simple Remote
	Night Glow Function On Remote Buttons	Yes	No	No	No	No	No	No	No

WAC - 3 STAR

Model No.		3W12GA	3WAE121YD	3W18LB	3W18GA	3WAE181YD
Performance Parameters	Nominal Capacity (TR)	1.0	1.0	1.5	1.5	1.5
	Voltage / Frequency / Phase	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single
	Cooling Capacity (Watt)	3250	3475	5030	4900	5120
	Power Input (Watt)	1115	1195	1730	1685	1750
	EER (W / W)	2.91	2.91	2.91	2.91	2.93
	Star Rating - BEE Table 2.4	3 STAR	3 STAR	3 STAR	3 STAR	3 STAR
	Running Current (Amps)	4.76	5.3	7.9	7.05	8.1
	Moisture Removal (Litres/hour)	1.6	1.2	2.3	2.11	1.8
	Airflow Volume (Wet CFM) (High / Medium/ Low)	236 / 227 / 218	255 / 230 / 205	460 / 420 / 380	430 / 418 / 398	440 / 395 / 350
Noise Level Indoor (High / Med / Low) In dB(A)	51 / 49 / 47	53 / 50 / 47	55 / 53 / 52	52 / 50 / 48	55 / 51 / 47	
Dimensions and Weight	Dimension (W X H X D) mm	600 x 385 x 525	600 x 380 x 560	660 x 430 x 760	660 x 430 x 770	660 x 428 x 680
	Net Weight	41 Kg	40 Kg	58.5 Kg	58 Kg	56 Kg
Compressor	Compressor Type	Rotary	Rotary	Rotary	Rotary	Rotary
	Compressor Warranty	5 Years	5 Years	5 Years	5 Years	5 Years
Refrigerant and Ambient Operations	Refrigerant	R 22	R 22	R 22	R 22	R 22
	Max. Ambient Temp (°C)	46°C	46°C	46°C	46°C	46°C
Remote	Remote	LCD Remote	LCD Remote	Simple Remote	LCD Remote	LCD Remote
	Night Glow Function On Remote Buttons	No	Yes	No	No	Yes

TECHNICAL SPECIFICATIONS

WAC - 5 STAR

Model No.		5W12GA	5W12LA	5W18GA	5W18LA
Performance	Nominal Capacity (TR)	1.0	1.0	1.5	1.5
Parameters	Voltage / Frequency / Phase	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single	230 V / 50Hz / Single
	Cooling Capacity (Watt)	3800	3590	4975	5060
	Power Input (Watt)	1135	1085	1505	1530
	EER (W / W)	3.35	3.31	3.31	3.31
	Star Rating - BEE Table 2.4	5 STAR	5 STAR	5 STAR	5 STAR
	Running Current (Amps)	4.78	4.75	6.54	6.80
	Moisture Removal (Litres/hour)	2.06	1.4	2.06	2.1
	Air Flow Volume (Wet CFM) (High / Medium/ Low)	430 / 418 / 398	325 / 305 / 285	430 / 418 / 398	385 / 368 / 355
	Noise Level Indoor (High / Med / Low) In dB(A)	52 / 50 / 48	52 / 50 / 48	52 / 50 / 48	59 / 52 / 50
	Dimensions & Weight	Dimension (W X H X D) mm	660 X 430 X 770	660 X 430 X 703	660 X 430 X 770
Net Weight		55 Kg	49 Kg	58 Kg	57 Kg
Compressor	Compressor Type	Rotary	Rotary	Rotary	Rotary
	Compressor Warranty	5 Years	5 Years	5 Years	5 Years
Refrigerant & Ambient Operations	Refrigerant	R 22	R 22	R 22	R 22
	Max Ambient Temp °C	46°C	46°C	46°C	46°C
Remote	Remote	LCD Remote	Simple Remote	LCD Remote	Simple Remote
	Night Glow Function On Remote Buttons	No	No	No	No



BLUE STAR

NOBODY COOLS BETTER™

For more information, email: coolingsolutions@bluestarindia.com or visit us at www.bluestarindia.com or SMS 'COOL' to 57575